

S/NO.	PART NO	DESCRIPTION	AVAILABLE
		Long Radius bends	QTY (PCS)
1	02S206430	SB SS 2.000" OD 16 GA, 90 DEG, 30" CLR, STD TANGENTS	10
2	02S256430	SB SS 2.500" OD 16 GA, 90 DEG, 30" CLR, STD TANGENTS	20
3	01S256436	SB SS 2.500" OD 16 GA, 90 DEG, 36" CLR, STD TANGENTS	100
4	01S306436	SB SS 3.000" OD 16 GA, 90 DEG, 36" CLR, STD TANGENTS	74
5	02S406430	SB SS 4.000" OD 16 GA, 90 DEG, 30" CLR, STD TANGENTS	25
6	01S406436	SB SS 4.000" OD 16 GA, 90 DEG, 36" CLR, STD TANGENTS	124
7	01S406448	SB SS 4.000" OD 16 GA, 90 DEG, 48" CLR, STD TANGENTS	150
		Galvanized Steel Couplings	
8	0102003W4	2-3C-OD FOR 2.00 OD-50.8MM	200
9	0102373W4	2-3C FOR 2.37 OD-60.3MM	185
10	0102503W4	2-1/2-3C-OD FOR 2.50 OD-63.5MM	0
11	0103003W4	3-3C-OD FOR 3.00 OD-76.2MM	361
12	0103503W4	3-3C FOR 3.50 OD-88.9MM	0
13	0104003W4	3-1/2-3C FOR 4.00 OD-101.6MM	139
14	0104503W4	4-3C FOR 4.50 OD-114.3MM	18
15	0105003W4	4-1/2-3C FOR 5.00 OD-127MM	100
16	0106003W4	6-3C-OD FOR 6.00 OD-152.4MM	99
17	0104503B3FG	4-3C FOR 4.50 OD-114.3MM	25
18	0104003B3FG	3-1/2-3C FOR 4.00 OD-101.6MM	25
19	0102003W3	2-3C-OD FOR 2.00 OD-50.8MM	249
20	0102503W3	2-1/2-3C-OD FOR 2.50 OD-63.5MM	274
21	0103003W3	3-3C-OD FOR 3.00 OD-76.2MM	180
22	0103503W3	3-3C FOR 3.50 OD-88.9MM	35
23	0104003W3	3-1/2-3C FOR 4.00 OD-101.6MM	3
24	0105503W2	5-1/2-3C OD FOR 5.50 OD - 139.7MM	100

NOTE:

MATERIAL OF CONSTRUCTION: 16 GAUGE (1.6MM) IN STAINLESS STEEL T304 ASTM A249 WITH MILL FINISH